

dimensions working position

WILLIBALD

Transport Dimensions (I/w/h)	mm	8350/25	8350/2530/3380	
Motor		Standard	Upgrade	
Manufacturer		Perkins	Perkins	
Туре		1204J-E44TTA	1204J-E44TTA	
maximum Performance	kW/HP	130/176	140/190	
Cylinder Quantity	pieces	R4	R4	
Capacity	CC	4400	4400	
Nominal Rotation Speed	rpm	1400-2200	1400-2000	
Rotation Speed at maximal Torque	rpm	1400	1400	
maximum Torque	Nm	750	815	
Emission		ECE STAGE V		
CO2 - Emission (NRTC)	(g/kWh)	673,76		
Fuel capacity	1	130		
AdBlue capacity	I	19		
chassis	2-	axle-central carriage, for 80 km/h according to StVZO		
Permissible Total Weight	kg	10000		
Rotor variant	#	V1		
Weight equipped	kg	approx. 550		
Width	mm	1250		
Diameter	mm	70	00	
maximal Rotation Speed	rpm	1550	1800	
Flails	Stk.	18		
Flail weight	kg	approx. 3,5		
Milling Stips / Scrapers	pieces	6 / 0		
Endless Floor	#	speed adjustable continuously		
Infeed Roller	#	speed adjustable continuously on throttle		
maximal Infeed Height	mm	300		
Rakes and Screens	#	position adjustable seper	etely with remote contr	
Discharge Conveyor (rubber band)	#			
Dropping Height	mm	2700		
Width	mm	1200		
Speed	m/sec	maximum 4,5		
Crawler Drive	#			
Speed	m/s	0,	1	



Outputs		
Green Waste	m³/h	up to 60
Matured Timber	m³/h	up to 40
Matured Timber (already fractured)	m³/h	up to 60
Bark	m³/h	up to 60
Livestock excrement (e.g. horse manure)	m³/h	up to 50

Configuration		
hydr. Hood Opening		•
Big one-piece Hood		•
Available Size of Screens:		
rhombas 40, 60, 80, 100, 145, 200, Cross		
Air brake system, with ABS		•
Drawbar Eye (50mm)		•
Load Sensing hydraulic system		•
24 Voltage Lighting System		•
exhaust gas treatment DOC / DPF / SCR		•
Reversible Fan	#	•
hydr. Support Wheel	#	•
crawler chassis	#	•
Stationary / semi-mobile 1-axle chassis / electric version 90 KW		0
Discharge Conveyor (rubber / hydr. foldable 2,7m)	#	o
Magnetic Guide Roller (Neodym)		0
Band security package		0
Crawler Drive	#	0
Remote Control		o
Central Lubrication		0
hydr. Axle Extractor	#	o
LED-Working Lights (4 pieces)	#	0
Water Spray System		o
hydr. foldable extended hopper		o
Drawbar Eye Extention		o
Special Paint		0
Duomatic - coupling		o
Biological Oil		0

• series

° option

all positions pointed out with # can be operate by optional remote control